

POLYSAFE VOGUE ULTRA

- A range of 12 decorative colours with coordinating chip and special surface finish.
- Coloured quartz, aluminium oxide and silicon carbide particles incorporated throughout the full thickness of the vinyl to improve traction and safety underfoot.

SPECIFICATION



2.0mm



2m x 20m = 40m²



2400g/m²



GENERAL PERFORMANCE

EN 13845

ASTM F1303

Agrément – G5ws



REACTION TO FIRE

EN 13501-1 Class Bfl-S1

{ EN ISO 9239-1 ≥8kw/m²
EN ISO 11925-2 Pass

ASTM E648 Class 1



ENHANCED SLIP

Sustainable wet slip resistance*

AS/NZS 4586 R10

EN 13845 ESf

RRL Pendulum Test ≥36 (wet test - 4S Rubber)

Surface roughness R_{tm} ≥ 20µm

The slip resistance across all Polyflor products is assured throughout the guaranteed life of the product.



ABRASION RESISTANCE

EN 13845 50,000 cycles

EN 649 Group T



VOC EMISSIONS

AgBB VOC test : Pass
(Low Result)



RESISTANCE TO CHEMICALS

Polysafe Vogue Ultra has good resistance to dilute acids and alkalis.

The Polyflor Technical Information Manual provides a general guide. Chemical resistance charts by shade are available on request.



HYGIENE

Contains antimicrobial agents for improved hygiene protection.

This product has been independently tested and results demonstrate that it inhibits the growth of MRSA. An effective cleaning regime is however, the most important defence against infection.



ELECTRICAL BEHAVIOUR (body voltage)

EN 1815 This product does not accumulate static charges above 2kV and is classified as 'antistatic'. For specialist applications where there is a requirement to dissipate the electrostatic charge, see the Polyflor ESD product ranges.



APPLICATIONS

Polysafe Vogue Ultra is designed for use in areas where enhanced slip resistance is an important consideration. Typical areas include washrooms, bars, food preparation areas, changing rooms, laundry and sluice rooms, canteens and institutional applications. For continually wet areas please refer to our Polysafe Hydro range. As with all Polysafe products, Polysafe Vogue Ultra should not have a polish applied.



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor.

At the date of issue the data presented is correct.

However, Polyflor Ltd. reserves the right to make changes which do not adversely affect performance or quality.

* For clarification regarding slip resistance, consult Polyflor.



POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM
UK SAMPLE REQUESTS: +44 (0)161 767 2551

James Nuttall
FLOORING




January 2007

POLYFLOR

POLYSAFE VOGUE ULTRA

SAFETY FLOORING

PERFORMANCE AND PROPERTIES



POLYFLOR
COVERING THE WORLD