

quickgrip

Water-based neoprene adhesive

DESCRIPTION

quickgrip is a multipurpose gap-filling adhesive, which has instant grab, fast cure, high-strength bond and is easy to gun.

USES

quickgrip is a multipurpose gap-filling adhesive, which is suitable for bonding most porous and non-porous surfaces, including plastic, wood, concrete, brick, plasterboard, GRP, carpets and metals.

FEATURES & BENEFITS

- **quickgrip** has instant grab properties and cures to form a high-strength bond, which makes it ideal for fixing plasterboard to timber panels, dado rails, door surrounds, worktops, ceramics, skirting boards, general DIY, and repairs.
- It is also ideal for filling gaps between uneven surfaces.

SURFACE PREPARATION

All surfaces must be clean dry and sound.

BONDING / PRIMING

No special primers are required.

MIXING

quickgrip must be used straight from the cartridge.

COVERAGE

Depending on thickness applied but would do approximately 8,6 m per 310 ml cartridge on a 6 mm x 6 mm application.

APPLICATION

Remove nozzle and cut off end of cartridge. Cut nozzle to required width

TYPICAL PHYSICAL PROPERTIES

Consistency	Thick paste
Slump	Nil
Shrinkage	Approx. 16%
Staining	None
Tack-free time	5 minutes
Water resistance	Good when fully cured
Bond strength	1 000 kPa

of bead and screw back on to cartridge. Place cartridge in cartridge gun. After application, surfaces must be firmly pressed together. The weight of the panels should be supported while the adhesive cures. For heavier objects, or while surfaces are uneven, it may be necessary to support the fixture initially with panel pins. **quickgrip** should only be used on sealed surfaces.

CLEANING

Tools, brushes and mixing equipment should be cleaned immediately after use and before material has set with **abe super brush cleaner** followed by washing with soap and water.

PROTECTION ON COMPLETION

No special protection required.

TEMPERATURE AND RELATIVE HUMIDITY

Application temperature range: +5° C - +35° C

MODEL SPECIFICATION

A multipurpose, gap-filling adhesive for high-strength bonding of most porous and non-porous surfaces.

The adhesive will be **quickgrip SF**, a one-component, gun-grade, solvent-free adhesive applied in accordance

with the recommendations of **abe Construction Chemicals**.

PACKAGING

quickgrip is available in a 310 ml cartridge packed in boxes of 12.

HANDLING & STORAGE

This product has a shelf life of 12 months if kept in a dry cool place in the original packaging. In more extreme conditions this period might be shortened.

HEALTH & SAFETY

quickgrip should not be allowed contact with skin and eyes. The use of gloves and eye protection is advised. Splashes into eyes should be washed immediately with plenty of clean water and medical advice sought.

Cured **quickgrip** is inert and harmless.

IMPORTANT NOTE

This data sheet is issued as a guide to the use of the product(s) concerned. Whilst **abe Construction Chemicals** endeavours to ensure that any advice, recommendation, specification or information is accurate and correct, the company cannot - because **abe** has no direct or continuous control over where and how **abe** products are applied - accept any liability either directly or indirectly arising from the use of **abe** products, whether or not in accordance with any advice, specification, recommendation, or information given by the company.

FURTHER INFORMATION

Where other products are to be used in conjunction with this material, the relevant technical data sheets should be consulted to determine total requirements. **abe Construction Chemicals** has a wealth of technical and practical experience built up over

Revision 9203



abe is an ISO 9002 Registered Company.

Technical data sheet

abe Construction Chemicals (Pty) Ltd. P.O. Box 23053, Isipingo, 4110, South Africa. 7 Wilcox Road, Isipingo, 4110 Tel. (031) 913 5400

years in the company's pursuit of
excellence in building and construction
technology.

Revision 9203



a b e is an ISO 9002 Registered Company.

Technical data sheet

a b e Construction Chemicals (Pty) Ltd. P.O. Box 23053, Isipingo, 4110, South Africa. 7 Wilcox Road, Isipingo, 4110 Tel. (031) 913 5400