

WATERPROOFING



PRODUCT USES

An acrylic waterproofing paint developed to be used with a mesh membrane. This product can be used on flashing, roof joins, roof screws, parapets and chimney cappings. Dulux waterproofing is not suitable for areas of long term ponding.



FEATURES AND BENEFITS

- Excellent Adhesion.
- Water Resistance.
- Flexible and Durable.
- Can be applied with Brush, Roller.



PRODUCT INFORMATION

Type	Acrylic Based
Drying Time	30 minutes between coats at 25 degrees Hard Dry : 12 - 24 hours
Coverage porosity	Approx. 2 - 3 m ² /litre depending at surface
Viscosity	100 KU
Finish	Matt
Specific Gravity	+/-1.2 Std SG setting (depending on colour)
Colour	White, Green, Red, Grey, Charcoal, Terracotta and Black



APPLICATION INFORMATION

Mix paint well before use, ensuring that the paint is homogenous.

1st Coat – Roll or Brush a thick coat of Dulux Waterproofing (1 litre/m). Work the membrane into the wet coat by using a roller or a stiff brush, avoiding the formation of bubbles or creases in the material. On flat surface. Membrane overlaps should be a minimum of 100 mm between 2 layers. Allow a minimum drying period of 30 minutes before applying second coat.

2nd Coat – Once the first coat has dried sufficiently to take working traffic (2 – 3 hours depending upon weather), apply a second coat of Dulux Waterproofing paint (0,7 litre/m) to ensure the membrane is completely wet.

3rd Coat – Once the second coat is dry, apply a final coat of Dulux Waterproofing paint at the rate of coat (0,7 litre/m).

AFTER PAINTING

Remove as much paint as possible from the brush by wiping the brush on the side of the container letting the Excess.

Clean equipment immediately with water.

Do not clean surface within 7 days of applying.

PAINTING ENVIRONMENT

Surface/ambient temperature: min: 10°C max: 35°C.

Relative humidity: 80% max.

Exterior
Waterproofing
paint developed
to be used with
mesh membrane





SURFACE PREPARATION

All surfaces must be clean and dry. All signs of fungus must be removed and surface sterilised with household bleach.

NEW SURFACES

Walls: Plaster and concrete surfaces

If loose and friable, apply one coat **Dulux Primer Sealer** (bonding liquid).
If sound, clean and apply direct to surface.

Roofs: Cement tiles and fibre cement

If loose and friable, apply one coat **Dulux Primer Sealer** (bonding liquid). If sound, clean and apply direct to surface.

Parapets and flat concrete roofs

If loose and friable, apply one coat **Dulux Primer Sealer** (bonding liquid). If sound, clean and apply direct to surface.

Mild steel surfaces

Remove any rust by wire brushing to a bright metal finish. Prime with one coat **Dulux Primer for Steel**.

Galvanised steel surfaces

New and weathered galvanised steel must be cleaned with **Dulux Cleaner** for Galvanised Iron and then primed with one coat **Dulux Primer for Galvanised Iron**.

PREVIOUSLY PAINTED SURFACES

All loose and flaking paint must be removed with a scraper. Exposed surfaces must be treated as per "new surfaces" above.



HEALTH AND SAFETY INFORMATION

PRECAUTIONS

Refer to Material Safety Data Sheet (E1140004X)
(White and Colours for safety precautions).

Store away from direct sun, heat and severe cold.

FLASHPOINT

Non-Flammable.



ADDITIONAL INFORMATION

DISCLAIMER

Colour swatch references are as accurate as printing will allow. For best colour and sheen consistency, it is advisable to use containers of the same batch number, in case of different batch containers it is recommended that they be mixed together in a large container or finish in a corner before starting a new container.



5L