



INTERIOR CRACK FILLER



PRODUCT USES

Fixit Interior Crackfiller is recommended for filling irregularities in all interior cement, gypsum plaster, soft board and fibre cement surfaces. Wood grain filling can be done with a thinner mixture, applied by brush.



FEATURES AND BENEFITS

Dries quickly – can be over painted with water based paint within 1 hour, and with solvent based paint in 4 hours.

Easy to use – excellent results are achieved by the average D-I-Y enthusiast.



PRODUCT INFORMATION

Physical State	White Powder.
Flash Point	Non flash.
Density at 23°C	N/A.
Water Miscibility	Almost Insoluble.
Odour	N/A.



APPLICATION INFORMATION

Application methods	Putty knife or small trowel
Thinner	None required except tap water to adjust consistency
Recoating Time	18 hours
Cleaning of equipment	Clean immediately with water
Substrates	Suitable for cement plaster, gypsum plaster, concrete, fibre cement and all composition boarding and wood.

Versatile white interior crackfiller for cracks, holes, ceiling joints and gaps around doors





APPLICATION INFORMATION

Precautions

Surfaces must be clean and dry. Remove all loose plaster, dust, old paint and wallpaper by brushing with a stiff wire brush. Narrow cracks are best widened with a sharp tool to ensure effective filling.

Do not apply during cold (below 10°C) or wet weather.

Not suitable for metal surfaces.

Not suitable for direct application to powdery or friable surfaces whether previously painted or not.

Not recommended for exterior use.

Not designed to repair or fix up faulty masonry, where obvious structural defects are apparent.

Always use clean utensils, and ensure the mixing vessel or surface has no residues of old, mixed Crackfiller.

To prolong shelf life, reseal packet after use, and store in a cool, dry place.

Mixing

Add approximately 3 parts powder into 2 parts water, and mix to a stiff but workable paste. Ensure that the paste is smooth, and that all lumps have been dispersed. Do not mix more paste than can be used within about one hour.

Application

Apply with a putty knife or small trowel, forcing the mixed paste well into the gaps or cavities. For deep cavities, use two or more applications, allowing each layer to harden before applying the next. Rinse the knife or trowel, and while still wet, smooth off the paste. Allow setting completely (preferably overnight for deep cavities), sandpaper smooth if necessary, remove all dust, and paint when dry.

Over Coating

Allow the **Fixit Interior Crackfiller** to dry thoroughly (preferably overnight) before painting. Water based (PVA) paints can be applied once the surface feels dry. Sandpaper off any irregularities, dust off and for oil paints, apply a coat of Alkali Resisting Primer over the filled areas. Allow to dry, and finish with your chosen top coat.



HEALTH AND SAFETY INFORMATION

For detailed safety information refer to Material Safety Data Sheet.

Keep out of reach of children.

Ensure good ventilation during application and drying.

Non-flammable.



ADDITIONAL INFORMATION

Storage Conditions

Store under cool dry conditions.



10kg

2kg

500g