

MATERIAL SAFETY DATA SHEET

Page: 1

NAME: FIXIT MULTIPURPOSE CRACK FILLER**REF. CODE: F684-3100**

DATE: 2009-10-14

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION

NAME: FIXIT MULTIPURPOSE CRACK FILLER

CODE: F684-3100

SUPPLIER: ICI DULUX (PTY) LTD; PAINTS PLACE; DICKENS ROAD; UMBOGINTWINI; 4126.

PHONE NUMBERS: 011-861-1000; 031-904-8000. FAX NUMBERS: 011-908-5204; 031-904-8196

C.A.S. No.: N/A EC No.: E.C. LABEL: ECOCHEM REF.: 32.50.00

UN/SIN No.: N/A

EAC:

HAZCHEM: INERT

HAZARD RATING

N N 1

SAPMA: 4-H-B

TREAT AS NUISANCE PARTICULATE.

IN EMERGENCY CONTACT: JOHN REID AT PHONE: 011 861 1235

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

EC CLASSIFICATION: NOT CLASSIFIED

OEL.TWA: 10/5mg/m² RL Total Dust / Respirable Dust

NO HAZARDOUS SUBSTANCES PRESENT

See Section 15 for full text of R (risk) and S (safety) phrases. RL = recommended limit; *S = skin absorption

SECTION 3. HAZARDS IDENTIFICATION

SAPMA HEALTH RATING: 4-MINIMAL - No great risk to health.

INHALATION: Excessive exposure to dust can cause lung damage.

SKIN: Direct contact to be avoided.

EYES: Particles may scratch eye or cause mechanical irritation.

INGESTION: No direct hazard expected but exercise caution.

NO CARCINOGENIC, MUTAGENIC OR GENETIC EFFECTS ESTABLISHED

May have short-term environmental effects. Contain, monitor & remove.

SECTION 4. FIRST AID MEASURES

INHALATION: Move to fresh air

SKIN: Always wash after being in contact with chemical substances.

EYES: Rinse immediately with plenty of water. Get medical attention if discomfort persists.

INGESTION: Seek medical advice in case of discomfort.

SECTION 5. FIRE FIGHTING MEASURES

FIRE RATING: NON-COMBUSTIBLE

EXPLOSION: No direct explosion hazard expected.

REACTIVITY: Inert substance.

SECTION 6. ACCIDENTAL RELEASE MEASURES - SEE ALSO SECTIONS 5,8 & 13
CONTAIN & COLLECT.

SECTION 7. HANDLING AND STORAGE

Ensure that this substance is kept dry at all times.

Inert substance No explosion hazard expected.

This MSDS conforms to SABS ISO 11014-1:1994 (ISO 11014/ANSI Z400.1.1996)

OELs derived from OHS Act Regulations for Dangerous Chemical Substances dated 25 August 1995 (EH-42)

SAPMA Rating - South African Paint Manufacturers Association Guide to Health Hazards (SABS ARP 006:1991).

NAME: FIXIT MULTIPURPOSE CRACK FILLER

REF. CODE: F684-3100

DATE: 2009-10-14

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

OEL.TWA: 10/5 mg/m² RL TYPE: Total dust/respirable dust

SAPMA RATING: 4-H-B PPE: Dust mask

INHALATION: Avoid breathing dust - use a mask.

SKIN: Observe the rules of hygiene. Wash before eating, drinking or smoking.

EYES: Avoid contact with dust. Use goggles. Never touch eyes with dirty hands or gloves.

INGESTION: Observe the rules of hygiene. Wash before eating, drinking or smoking.

GENERAL: Appropriate hand protection and protective clothing must always be used

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

CHEMICAL CLASS: Mixed Inorganic/organic powder

APPEARANCE: WHITE POWDER

SOLUBILITY: WATER: Almost insoluble, but reacts.

SECTION 10. STABILITY AND REACTIVITY

STATIC: Could produce static discharge - use earthing

STABILITY: Stable if stored under normal conditions.

SECTION 11. TOXICOLOGICAL INFORMATION

NO CARCINOGENIC, MUTAGENIC OR GENETIC EFFECTS ESTABLISHED

LD₅₀ ORAL: mg/kg LD₅₀ SKIN: mg/kg LC₅₀ INHALATION: mg

SECTION 12. ECOLOGICAL INFORMATION

May have short-term environmental effects. Contain, monitor & remove.

SECTION 13. DISPOSAL CONSIDERATIONS

Minimal hazard. No problems contemplated in disposal. Avoid creating dust when disposing of used bags.

SECTION 14. TRANSPORT INFORMATION

UN No.: NONE PACKING GROUP: N/A HAZCHEM CODE: INERT EA CODE:

IMO CLASS:

SECTION 15. REGULATORY INFORMATION

EC INDEX No.: EEC LABEL No. (EINECS/ELINCS):

S22 Do not breathe dust

SECTION 16. OTHER INFORMATION

IN CASE OF ANY DISCOMFORT ALWAYS SEEK MEDICAL ADVICE.

All information is given in good faith but without guarantee in respect of accuracy.
No responsibility is accepted for errors or omissions or the consequences thereof.