



## MULTI PURPOSE CRACK FILLER - READY MIXED



### PRODUCT USES

It sets in 60 minutes to a grey weatherproof finish that will accept bolts and screws without shrinking or cracking.



### FEATURES AND BENEFITS

It is formulated to give a tough weatherproof finish.

It is suitable for all exterior filling jobs i.e. masonry, concrete, brickwork and paving.

It sets to a grey, weatherproof finish in 60 minutes.

It accepts bolts and screws and will not shrink or crack. It is drillable.

Easy to use – excellent results are achieved by the average D-I-Y enthusiast.



### PRODUCT INFORMATION

<b>Density at 23°C</b>	Approx. : 1.27 kg/L
<b>Solids Content</b>	By weight : Approx. 47% By volume : Approx. 36%
<b>Packaged Viscosity</b>	Viscosity at 23°C : Approx 100 KU
<b>Volatile Organic Compound</b>	White 25g/L, colours 50g/L, and tint bases 21g/L - complies with EU regulations, Directive 2004/42/CE.
<b>Spreading Rate</b>	Varies with depth of imperfections
<b>Recommended DFT per coat</b>	Min. 25µm. Max. 35µm.



### APPLICATION INFORMATION

<b>Application Method</b>	Filling knife
<b>Thinner</b>	None required except tap water to adjust consistency
<b>Recoating Time</b>	6 hours but preferably overnight
<b>Clean up</b>	Water
<b>Substrates</b>	Suitable for masonry, concrete, brickwork and paving.

Tough exterior filler suitable for all exterior filling jobs



330g

500g

2kg



330g

500g

2kg



## APPLICATION INFORMATION

### Precautions

Ensure that surfaces are sound and free from dust, dirt, grease and oil. Surfaces must be thoroughly dry - no more than 12% moisture content.

Do not apply during cold (below 10°C) or wet weather.

Not suitable for direct application to powdery or friable surfaces whether previously painted or not.

Always use clean utensils, and ensure the mixing vessel or surface has no residues.

Store any unused powder in dry conditions.

To prolong shelf life, reseal packet after use, and store in a cool, dry place.

### Application

Remove the cap and squeeze the filler into a crack, and smooth off with a wet filling knife.

Ensure filler is level with the surface being filled.

For deeper repairs above 10mm – build up in layers allowing thorough drying between applications.

If necessary, sand down when fully dry.

It can be over painted when fully dry (preferably overnight).

### Overcoating

Allow the Fixit Multi Purpose Exterior to dry thoroughly (6 hours for gaps of 2 – 3 mm, but preferably overnight) before painting. Water based (PVA) paints can be applied once the surface feels dry. Sandpaper off any irregularities, dust off, and for oil paints, apply a coat of Alkali Resisting Primer over the filled areas. Allow to dry, and finish with your chosen top coat.



## HEALTH AND SAFETY INFORMATION

For detailed safety information refer to Material Safety Data Sheet.

Keep out of reach of children.

Ensure good ventilation during application and drying.

Non-flammable.



## ADDITIONAL INFORMATION

### Storage Conditions

Store under cool dry conditions.