

NAME: ROCKGRIP RFU ALUMINIUM

REF. CODE: R420-1503

DATE: 2011-12-29

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION

NAME: ROCKGRIP RFU ALUMINIUM PAINT

CODE: R420-1503

MANUFACTURER: ICI DULUX (PTY) LTD; PAINTS PLACE; DICKENS ROAD; UMBOGINTWINI; 4126.

PHONE NUMBERS: 011-861-1000; 031-904-8000. FAX NUMBERS: 011-908-5204; 031-904-8196

C.A.S. No.: PREPARATION

EC No.:

EC LABEL:

UN/SIN No.: 1263

EAC: 127

HAZCHEM: 3[Y]

HAZARD RATING: F N 3

SAPMA: 3-H-E

IN EMERGENCY CONTACT:

P MOODLEY

AT PHONE: 031 904 8164

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

EC CLASSIFICATION: XI, R10,43 S16,28,33,38

ALIPHATIC SOLVENT 25-50% CAS 8052-41-3 EEC Labels: F,R10

OEL: 575mg/m³ RL*S

NO OTHER HAZARDOUS COMPONENTS PRESENT

This product contains "NO ADDED LEAD" and measured Lead levels are below 90µg/g

See Section 15 for full text of R (risk) and S (safety) phrases. RL = recommended limit; *S = skin absorption

SECTION 3. HAZARDS IDENTIFICATION

SAPMA HEALTH RATING: 3-SLIGHT - Irritation or minor reversible injury possible.

INHALATION: Irritating, narcotic. Can affect CNS.

SKIN: Possible skin sensitiser. Irritating, risk of dermatitis. May be absorbed.

EYES: Irritating.

INGESTION: Irritating.

NO CARCINOGENIC, MUTAGENIC OR GENETIC EFFECTS ESTABLISHED

May have short-term environmental effects. Contain, monitor & remove.

SECTION 4. FIRST AID MEASURES

INHALATION: Move to fresh air. In case of discomfort seek medical attention.

SKIN: Use hand cleaner or plenty of soap and water. Remove contaminated clothing.

If any discomfort persists, seek medical advice.

EYES: Rinse immediately with plenty of water. Seek medical advice if symptoms persist.

INGESTION: Give plenty of water or milk. DO NOT INDUCE VOMITING! Seek medical advice.

SECTION 5. FIRE FIGHTING MEASURES

FIRE RATING: Flammable - Flash point < 63°C

REACTIVITY: Inert - No reaction with fire-fighting water.

EXTINGUISH: Foam. CO₂. Dry powder. Fog to cool and control. Do NOT use water jets.

EXPLOSION: Cool containers in case of fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES - SEE ALSO SECTIONS 5,8 & 13

CONTAIN & COLLECT. KEEP OUT OF DRAINS & SEWERS.

SECTION 7. HANDLING AND STORAGE

STORAGE: Store separately from any reactive substances - oxidisers in particular.

FIRE: No open flames. No smoking.

EXPLOSION: Keep containers cool. Avoid free fall of liquid - use earthing.

NAME: ROCKGRIP RFU ALUMINIUM PAINT

CODE: R420 1503

DATE: 2011-12-29

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

OEL.TWA: 100ppm TYPE: Mixture See Section 2 "Skin"
SAPMA RATING: 3-H-E PPE: Respirator & suitable eye protection
INHALATION: In case of insufficient ventilation, use suitable respiratory protection.
SKIN: Possible skin sensitiser. Use barrier cream and impervious gloves.
EYES: Use face shield & goggles or full-face respirator/hood. Avoid direct contact.
INGESTION: Observe the rules of hygiene. Wash before eating, drinking or smoking.
GENERAL: Appropriate hand protection and protective clothing must always be used.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

CHEMICAL CLASS: PAINT PRODUCT
APPEARANCE: SILVER VISCOUS LIQUID ODOUR: PUNGENT
pH: N/A DENSITY: 0.90 – 0.93 NON-VOLATILE: 50 - 53%
FLASH POINT: 37°C TCC EXPLOSIVITY: 1.0 /8.7 %
VISCOSITY: 23 - 28 sec Ford #4 @ 23°C BOILING RANGE: 160 - 200°C
SOLUBILITY: WATER: Insoluble OIL: Miscible
PARTITION COEFFICIENT (N-OCTANOL/WATER): N/E CONDUCTIVITY: N/A

SECTION 10. STABILITY AND REACTIVITY

STATIC: Could produce static discharge - use earthing
STABILITY: Stable if stored under normal conditions. Hazardous polymerisation will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION

NO CARCINOGENIC, MUTAGENIC OR GENETIC EFFECTS ESTABLISHED

Possible skin sensitiser

LD₅₀ ORAL: mg/kg (rat) LD₅₀ SKIN: mg/kg (rabbit) LC₅₀ INHALATION: mg

SECTION 12. ECOLOGICAL INFORMATION

May have short-term environmental effects. Contain, monitor & remove.

SECTION 13. DISPOSAL CONSIDERATIONS

Hazardous. Use reputable waste disposal contractors. Destroy used containers.

SECTION 14. TRANSPORT INFORMATION

UN No.: 1263 PACKING GROUP: III HAZCHEM CODE: 3[Y] EA CODE: 127
IMO CLASS: 3.3 PAINT MARINE POLLUTANT CLASS: Y

SECTION 15. REGULATORY INFORMATION

EC INDEX No.: EEC LABEL No. (EINECS/ELINCS): XI Irritant

R10 Flammable
R43 May cause sensitisation by skin contact
S16 Keep away from sources of ignition - No smoking
S28 After contact with skin, wash immediately with soapy water, or use approved hand cleaner.
S33 Take precautionary measures against static discharges.
S38 In case of insufficient ventilation, wear suitable respiratory equipment

SECTION 16. OTHER INFORMATION

TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGES.

THIS SUBSTANCE IS A POTENTIAL SENSITISER - ENSURE PRECAUTIONS ARE TAKEN.
IN CASE OF ANY DISCOMFORT ALWAYS SEEK MEDICAL ADVICE.

All information is given in good faith but without guarantee in respect of accuracy.
No responsibility is accepted for errors or omissions or the consequences thereof.