

## COLOURS OF THE WORLD™



### PRODUCT USES

Colours of the World™ is an interior, low sheen and low odour washable paint for walls.



### FEATURES AND BENEFITS

Very good cleanability and wear resistance.

Very good coverage.

Low odour.

Superb appearance with an even low sheen finish.



### PRODUCT INFORMATION

<b>Appearance</b>	Low Sheen
<b>Colour</b>	A range of 25 ready mixed colours (Rich, Daring, Truly, Tender and Gentle)
<b>Density at 23°C</b>	Use an average 1.27 kg/L
<b>Solids Content</b>	By Mass: Approx. 46% By Volume: Approx 31%
<b>Packaged Viscosity</b>	Viscosity at 23°C : Approx 100 KU
<b>Spreading Rate</b>	Approx. 8 to 10 m <sup>2</sup> /litre depending on surface porosity, profile and application method
<b>Recommended DFT per coat</b>	Min. 30µm. Max. 35µm.
<b>VOC Level g/l</b>	Approx: 14g/l to 24g/l
<b>Packaging</b>	Rich and Daring colours (2.5L) Truly, Tender and Gentle colours (5L)



### APPLICATION INFORMATION

<b>Application conditions</b>	Surface Temperature between 10°C - 35°C Relative Humidity between 10 % - 85 %
<b>Application</b>	Brush, roller or airless spray
<b>Thinner</b>	Thinning not recommended Ready for use after thorough stirring
<b>Drying times</b>	Touch dry 60 minutes (Drying times will be extended during cold, wet or humid conditions)
<b>Recoating times</b>	4 hours
<b>Cleaning of equipment</b>	Clean immediately with water

Interior colour collection inspired by the world's most beautiful landscapes



\* Rich and Daring colours (2.5L)

\*\* Truly, Tender and Gentle colours (5L)



## APPLICATION INFORMATION

### Substrates

Suitable for cement plaster, gypsum plaster, concrete, fibre cement, ceiling boards and wooden surfaces provided the appropriate preparation is carried out.

### Precautions

Ensure that surfaces are sound and free from dust, dirt, grease and oil. Surfaces must be thoroughly dry - no more than 12% moisture content.

Do not apply during cold (below 10°C) or wet weather.

Do not apply directly to bare metal surfaces.

### Coats Required

Apply two to three finishing coats to achieve a closed film and solid colour.



## SURFACE PREPARATION

### NEW SURFACES

#### Cement Plaster (non friable), Gypsum Plaster, Composition Boarding, Fibre Cement

It is recommended that fresh plaster should be allowed one week drying for every 5mm thickness; and longer in cold or damp weather.

Spot-prime metal strips and nail heads with appropriate metal primer.

Prime with one full coat **Dulux Plaster Primer**.

Rough surfaces may be filled with **Dulux Trade Fillercoat/Dulux Smoothover** to create a smooth base of even porosity.

#### Concrete

Remove any uncured cement, grease and mould release agents by high-pressure water blast, or wash with a strong solution of sugar soap. Rinse off thoroughly with clean water.

Prime with one full coat **Dulux Plaster Primer**.

#### Wooden Surfaces

Prime with **Dulux Wood Primer**.

Alternatively, timber surfaces can be primed with **Dulux Supergrip** to give a complete water based system.

### PREVIOUSLY PAINTED SURFACES

#### Sound, not powdery

Clean surfaces with **Dulux Sugar Soap**. Wash down with water.

For emulsion surfaces apply finishing coats.

For enamel surfaces, sand to a matt finish to aid adhesion and follow with one coat of **Dulux Undercoat for All Surfaces**. Apply finishing coats.

#### Old Paint in poor condition

Strip loose and flaking paint completely and spot prime bare areas with **Dulux Plaster Primer**.

Friable and porous surfaces must be removed and repaired.

Mould instructions: To kill lichen and algae growth, scrub with one of the following solutions: either 25% chlorine solution and water or 25% bleach (sodium hypochlorite) and water solution. Ensure that the areas are completely saturated and allow the solution to react for a minimum of 4 hours. Rinse the complete wall surface thoroughly with clean water.

#### Filling

Fill all imperfections with the appropriate **Dulux filler** and spot prime filled areas with **Dulux Plaster Primer** once the crack filler has dried properly. Failure to do this will result in uneven sheen levels between the repaired and normal areas.



## HEALTH AND SAFETY INFORMATION

For detailed safety information refer to Material Safety Data Sheet.

Keep out of reach of children.

Ensure good ventilation during application and drying.

Non-flammable.



## ADDITIONAL INFORMATION

#### Storage Conditions

Store under cool dry conditions.

#### Disclaimers

Colour references are as accurate as printing will allow. Please refer to the in-store stripe cards/standard card, or on-shelf colour displays for an accurate representation of the colour.

Among others, the following factors may affect final colour appearance: product sheen and texture, colour and light reflections, application, surface texture and preparation.

For best colour and sheen consistency, it is advisable to use containers of the same batch number, to mix different batches together in a large container, or to finish in a corner before starting a new container.