



According to European Classification EN 685



Safetred Safety Floorings

DESCRIPTION

Slip resistant heavy duty floorcoverings with Safety Clean PUR reinforcement, in sheet format.
Product standard: EN 13845.

| Technical data | Standards | Safetred Dimension | Safetred Spectrum | Safetred Universal |
|--|--|---|---|---|
| Certification | EN 685 commercial industrial EN 13845 | Classes: 34 43 ES _f | Classes: 34 43 ES _f | Classes: 34 43 ES _f |
| Total thickness | EN 428 | 2.00 mm | 2.00 mm | 2.00 mm |
| Total weight | EN 430 | 2 500 g/m ² | 2 400 g/m ² | 2 600 g/m ² |
| Safety Clean PUR Reinforcement | | Yes | Yes | Yes |
| Abrasion Group | EN 660-2 | Class T | Class T | Class T |
| Static indentation | EN 433 | < 0.10 mm | < 0.10 mm | < 0.10 mm |
| Furniture leg | EN 424 | No damage | No damage | No damage |
| Castor chair | EN 425 | No damage | No damage | No damage |
| Dimensional stability | EN 434 | ≤ 0.10% | ≤ 0.10% | ≤ 0.10% |
| Curl resultant to heat | EN 434 | ≤ 8 mm | ≤ 2 mm | ≤ 2 mm |
| Flame and smoke | EN 13501-1 ISO 9239-1 Epiradiateur ASTM E648 ASTM E662 IMO A653 DIN 4102 Part 14 | B _{fl} s1 > 0.8 W/cm ² M3 Category 1 Pass Pass | B _{fl} s1 > 0.8 W/cm ² M3 Category 1 Pass Pass | B _{fl} s1 > 0.9 W/cm ² M3 Category 1 Pass Pass Class B2 |
| Slip resistance | TRRL Pendulum 4S DIN 51130 ASTM D2047 DIN 51097 | High slip resistance R10 > 0.8 | High slip resistance R10 > 0.8 | High slip resistance R10 > 0.91 B |
| Electrical resistance | EN 1815 EN 1081 EN 14041 | 2 kV > 10 ¹⁰ Ω on process | 2 kV > 10 ¹⁰ Ω on process | 2 kV > 10 ¹⁰ Ω on process |
| Impact sound reduction | EN ISO 140-8 EN ISO 717/2 ΔL _w | on process | on process | on process |
| Sonority | NF S 31-074 L _{n,e,w} | on process | on process | on process |
| Light fastness | EN ISO 105-B02 | 7 | 7 | 7 |
| Chemical resistance | EN 423 | Good resistance to everyday substances | | |
| Anti fungi treatment | | Incorporates a biostat to resist fungi and bacterial growth | | |
| Thermal resistance Underfloor heating | EN 12524 | 0.01 m ² K/W Suitable | 0.01 m ² K/W Suitable | 0.01 m ² K/W Suitable |
| Colours | | 16 | 20 | 16 |
| Form of delivery | EN 426 | Rolls: 20 lm X 2 m | | |

The above information is subject to modification for the benefit of further improvement (06/06). For more detailed technical information, please contact Tarkett. Follow Tarkett's installation and maintenance instructions carefully. These instructions are available upon request.