

FlowSport (7mm nominal)



Description

FlowSport is a composite surface specially designed and fabricated by Flowcrete creating a synthetic flexible sports flooring. When applied over a suitable base, it provides a resilient uniform seamless and durable surface for multi-use gymnasium and indoor sports venues. Court lines and area markings are applied in internationally recognised colours on top of the finished surfaces. (Please contact our Technical Advisors for details of specialist companies to supply line-marking).


Uses

Recommended for use in education and local authority sports halls, gymnasia and leisure centres. FlowSport provides a robust, aesthetically pleasing sporting environment underfoot offering longevity for any indoor sporting facility.

Benefits


- Cushioned effect – spring & give in the floor
- Attractive range of bright colours
- Eliminates glare and light reflection
- Resilient and flexible coating
- Hard wearing - abrasion and impact resistant finish
- Seamless hygienic surface, easy to clean and maintain
- Can be used in conjunction with Isowarm underfloor heating

Standard colour chart



The applied colours may differ slightly from the examples shown above. Contact our customer services for a true colour sample or a special colour match. Special corporate colours and designs can be produced to special order.

System Design



Model Specification

Product: FlowSport
Finish: Matt
Thickness: 7 mm dependant on specification.
Colour: _____
Manufacturer: Flowcrete SA (Pty) Ltd
Telephone: Customer Service - +27 31 461 3411

Preparatory work and application in accordance with suppliers instructions.

Substrate Requirements

Concrete or screed substrates should be a minimum of 25N/mm², free from laitance, dust and other contamination. The substrate should be dry to 75% RH as per BS8204 and free from rising damp and ground water pressure. If no damp proof membrane is present, Hydraseal DPM can be incorporated as the primer.

Products Included in this System

Primer: Flowseal EPW @ 0.2L/m²
Adhesive: Solvent Free Contact Adhesive @ 0.08 kg/m²
Mat: FlowSport Matting 5mm or 7 mm (as required)
Grout: @ 0.25 kg/m² (Flowshield LXP Primer)
(total for two coats or as required)
Bodycoat: **for 1 mm thickness**
Flowshield LXP @ 1L/m²
Or for 2 mm thickness
Flowshield LXP @ 2L/m²
Topcoat: Flowcoat UV @ 0.2L/m²

Detailed application instructions are available upon request.

NB: Specifications are written for each installation to meet the clients particular requirements.

Installation Service

The installation should be carried out by a Flowcrete approved contractor with a documented quality assurance scheme. Obtain details of our approved contractors by contacting our customer service team or enquiring via our web site www.flowcretesa.co.za.

Focus on the Floorzone

Flowcrete Group are world leaders in specialist industrial and commercial flooring. Systems available include: underfloor heating systems, floor screeds, surface damp proof membranes, decorative floor finishes, seamless terrazzo, car park deck waterproofing, tank lining systems... to name just a few.
Our objective is to satisfy your Floorzone needs.

Important Note

Flowcrete's products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and Conditions of Sale, copies of which can be obtained on request.

Technical Information

The figures that follow are typical properties achieved in laboratory tests at 20 °C and at 50% Relative Humidity.

Slip Resistance
Method described in BS 7976-2
(typical values for 4-S rubber slider)
Dry >50 low slip potential
(in accordance with HSE and UKSRG guidelines)

The slipperiness of flooring materials can change significantly, due to the installation process, after short periods of use, due to inappropriate maintenance or longer-term wear.

To meet slip resistance value requirements for wet conditions, textured systems are recommended - please contact our Technical Advisors for further details and specifications.

Temperature Resistance Tolerant up to 50°C
Water Permeability Nil - Karsten test (impermeable)
Chemical Resistance Good resistance to tea, coffee, cola, fruit juice, soaps and bleach.
Compression set 97-99% recovery typical after 72 hours at 50% compression at 20°C.
Abrasion resistance (for the Topcoat) Taber Abrasion –
Dry CS10/1000 cycles/1 kg – 80mg
Dry H18/1000 cycles/1 kg – 400 mg
Shore A Hardness 50
Bond Strength Inter-coat bond strength >2.0 MPa.

All above values are approximate and may be used as a guideline for specifications.

Speed of Cure (from final coat)

	10°C	20°C	30°C
Light traffic	36 hrs	24 hrs	12 hrs
Full traffic	72 hrs	48 hrs	24 hrs
Full chemical cure	12 days	7 days	7 days

Aftercare - Cleaning and Maintenance

Clean regularly using a single or double headed rotary scrubber drier in conjunction with a mildly alkaline detergent.

Life Expectancy

(3 years for the Topcoat wearing layer).
To prevent damage to the surface, choose suitably wheeled apparatus which has no sharp edges and is designed to achieve load distributions below 100psi.
Please contact our Technical Advisors for details of specialist companies to supply line-marking, which can be re-coated throughout the life of the FlowSport system.

Environmental considerations

The finished system is assessed as non-hazardous to health and the environment. The long service life and seamless surface reduce the need for repairs, maintenance and cleaning. Environmental and health considerations are controlled during manufacture and application of the products by Flowcrete staff and fully trained and experienced contractors.

Further Information

To ensure you are specifying a fit for purpose flooring for your project please consult our Technical Advisors on the number below or visit our website to register your interest in specifying one of the most durable floors on the market.

Flowcrete SA (Pty) Ltd (2003/029560/07)
176 Voortrekker Street Jacobs Durban 4052
Tel: +27 31 461 3411 Fax: +27 31 461 3475
47 Forge Road Spartan Kempton Park Johannesburg 1619
Tel: +27 11 394 1980 Fax: +27 11 394 3003
Unit 5 55 Manhattan Street Boquinar Industrial Area Matroosfontein Cape Town 7490
Tel: +27 21 385 0653 Fax: 0865 83 8358
Email: southafrica@flowcrete.com

www.flowcretesa.co.za