

PAINTCOR

SUPREME QUALITY *Since 1986*

2020 Revision

PRISTINA

Description and Application

CATEGORY

Wall Coating / Paint techniques / Wood paint

DESCRIPTION

Pristina Acrylic PVA is a quality emulsion paint suitable for interior and exterior use. Pristina has been formulated to the highest PVA specifications, is based on a pure acrylic and has a smooth matt finish.

FEATURES

- Creates an efficient breathable finish for substrates such as off-shutter concrete, asbestos, cement, fresh plaster and ceilings.
- It is non-yellowing, odourless, non-toxic and environmentally friendly.
- It is an excellent base-coat for paint techniques and is best used with Art-FX Scumble Glaze and Glaze Coat.
- It has very good hiding power.
- It is available in white and all colours.
- Good exterior durability.

AREAS OF USE

- Interior and Exterior walls
- Ceilings
- Paint techniques

SURFACE PREPARATION AND APPLICATION

NEW PLASTER

1. Remove all loose and friable materials.
2. If plaster is poor and under bound, apply one coat of Paintcor's AcrySeal acrylic sealer, diluted 1:1 with water. Allow to dry. Apply 1 coat of Paintcor's Acrylunder (only necessary for smoother finishes). Allow to dry followed by 2 coats of Pristina allowing 1 hour @ 25 degrees C to dry between coats
3. If the plaster is of good quality, apply one coat of Paintcor's PlasterPrime. Allow sufficient time to dry.

Paintcor cc

Reg No: CK 86/19456/23
VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sales@paintcor.co.za

Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955

Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 CERTIFIED



PAINTCOR

SUPREME QUALITY *Since 1986*

4. Apply two coats of Pristina. Allow 1 hour @ 25 degrees C to dry between coats.

PREVIOUSLY PAINTED PLASTER

Check the adhesion strength of the existing paint using the cross-hatch method.

1. Using a Stanley knife to cut through the paint surface. Do this vertically and horizontally to the substrate, approximately 3mm apart, creating little squares.
2. If the edges of the squares curl up, and the square can easily be removed, this means the adhesion of the old paint system is failing.
3. Remove all old paint back to existing plaster.
4. If surface is powdery or chalking, wash surface to remove all powder. Allow sufficient time to dry.
5. Apply one coat of Paintcor's AcrySeal acrylic sealer diluted 1:1 with water to all exposed plaster and washed chalking surfaces. Allow sufficient time to dry.
6. Spot prime the sealed exposed plaster with one coat of Paintcor's Acrylunder to help prevent an uneven finish. Allow to dry
7. Finally apply two coats of Pristina. Allow sufficient time to dry in between coats.

If adhesion is good:

1. Wash the walls down to remove all dirt, dust and chalk, allowing to dry. Should there still be slight chalk deposits on the wall then apply 1 coat of Paintcor's AcrySeal Acrylic Sealer diluted 1:1 with water to the entire surface to be painted. Allow to dry.
2. Apply two coats of Pristina. Allow sufficient time to dry in between coats.

APPLICATION EQUIPMENT

Apply by Brush, Sheepskin/Synthetic Roller or Spray

CLEANING EQUIPMENT

Clean all equipment with water immediately after use.

STORAGE

Keep stored in cool, dry conditions and away from children