

PAINTCOR

SUPREME QUALITY *Since 1986*

2020 Revision

STONESEAL

Description and Application

CATEGORY

Sealer

DESCRIPTION

StoneSeal is a specially formulated brick and stone sealer with excellent adhesion, UV protection and water resistance. It has been designed to penetrate deep into the applied surface, enhancing the rich natural colour of the brick or stone whilst protecting and sealing it.

FEATURES

- Protects against UV rays.
- Excellent water resistance.
- Excellent adhesion.
- Enhances the natural colour of brick or stone.
- Seals and protects the surface area from various weather conditions.
- Suitable for interior and exterior use.

AREAS OF USE

- Face bricks
- Stone Walls
- Slate Tiles
- Porous tiles

SURFACE PREPARATION AND APPLICATION

1. Ensure that the surface is dry and free of any old sealer, paint, dirt, grease, oil or loose particles.
2. Remove algae from the surface if necessary, using Paintcor's Ushevu algae killer (see Ushevu Data sheet).
3. Replace damaged or missing grouting.
4. Apply using a brush, roller or spray. StoneSeal is ready for use, no thinning is required.
5. First test product by applying to a small area, thereby ensuring the desired finish and colour.
6. Apply at least two coats to brick or stone. Allow approximately 4 hours drying time at 25 degrees C in between coats.
7. Clean all equipment with lacquer thinners immediately after use.

PAINTCOR

SUPREME QUALITY *Since 1986*

NOTE: Some brick and stone are more absorbent than others and a third coat may be necessary. More coats means better and longer protection and a gloss finish. Do not use in confined areas without the correct breathing equipment. Please first see the Material Safety and Technical Specification Data Sheets. Do not try and apply this product at a thick rate, rather use thin coats, allowing sufficient time to dry in between each coat.

APPLICATION EQUIPMENT

Brush, Mohair Roller or Spray.

CLEANING EQUIPMENT

Clean all equipment with mineral turpentine immediately after use.

STORAGE

Keep stored in cool, dry conditions and away from children. Flammable product, keep away from open flame.