

PAINTCOR

SUPREME QUALITY *Since 1986*

2020 Revision

ESSENCE

Technical Specifications

Vehicle Type	Pure Acrylic
Solvent	Water
Enviro Rating	2.8g/L of VOC (Conforms to Greenstar ratings)
Dilution / Thinning	Supplied ready for use
Theoretical Spread Rate	8m ² per litre
	NB: A MINIMUM OF 2 COATS TO BE APPLIED
Apply with	Brush, Roller or Spray
Drying time	@ 25°C ± 45 minutes per coat. Overcoat ± 1 hour
Wash ability	Good
Elongation	Good
Pigment	Pigmented
Solids Volume	28%
Flexibility	Good
Colour	Colour of your choice
Finish	Mild sheen
Storage	Cool, dry place.
Over coating	N/A
Packaging	1L, 5L and 20L
Guarantee	7 Years
Conditions of Guarantee	Product to be applied to manufacturers specifications. Areas below damp proof course, boundary walls and structural defects are not covered by this guarantee.
Resistance to Water	Good
Resistance to Solvents	N/A
Impact Resistance	Good
Active Ingredient	N/A
Additional Amount	N/A
Caution	Safe, Non-toxic, Non-flammable, Low VOC
Catalyst Ratio	N/A
Recommended Dry Film	30um (microns per coat, minimum 2 coats)
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	Pass
Appearance	Emulsion Paint

Note: VOC's are calculated on specific raw materials used in the product which contain VOC's, namely Glycol, Amine and free monomers.