

PAINTCOR

SUPREME QUALITY *Since 1986*

2020 Revision

SEALERMIX

Technical Specifications

Vehicle Type	Modified Acrylic
Solvent	Water
Enviro Rating	2.2g/L of VOC (Conforms to Greenstar ratings)
Dilution / Thinning	This product is NOT to be thinned
Theoretical Spread Rate	±8m ² per litre
Apply with	Brush, Roller or Spray
Drying time	@ 25°C ±20 minutes. Allow ±45 minutes before over coating.
Wash ability	N/A
Elongation	OK
Pigment	Pigmented
Solids Volume	N/A
Flexibility	Good
Colour	Can be tinted
Finish	Matt
Storage	Cool, dry place
Over coating	Top coat of your choice
Packaging	1L, 5L and 20L
Guarantee	N/A
Conditions of Guarantee	N/A
Resistance to Water	Good
Resistance to Solvents	Fair
Impact Resistance	N/A
Active Ingredient	N/A
Additional Amount	N/A
Caution	Safe, Non-Toxic, Non-Flammable
Catalyst Ratio	N/A
Recommended Dry Film	N/A
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	N/A
Appearance	White Emulsion Sealer

Note: Spread rates will vary according to porosity of the plaster. VOC's are calculated on specific raw materials used in the product which contain VOC's, namely Glycol, Amine and free monomers.

Paintcor cc

Reg No: CK 86/19456/23

VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sales@paintcor.co.za

Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955

Emergency Numbers
+27(0) 79 526 1585
+27(0) 84 305 5636



SABS
ISO 9001 CERTIFIED

