

POLYSAFE WOOD FX

- Heavy-duty safety flooring, featuring wood effect designs with slip resistance
- Fully HSE compliant
- Reinforced with polyurethane for improved cleaning and maintenance
- Ideal for busy front of house public areas such as receptions and corridors

SPECIFICATION



2.0mm



0.70mm



2m x 20m = 40m²



3000g/m²



GENERAL PERFORMANCE

EN 13845

ASTM F1303

Agrément - under application



REACTION TO FIRE

EN 13501-1 Class Bfl-S1

ASTM E648 Class 1

EN ISO 9239-1 ≥8kw/m²
EN ISO 11925-2 Pass



ENHANCED SLIP

Sustainable wet slip resistance*

AS/NZS 4586 R10

EN 13845 ESf

RRL Pendulum Test ≥36 (wet test - 4S Rubber/Slider 96)

Surface roughness Rz ≥20µm

The slip resistance across all Polysafe products is assured throughout the guaranteed life of the product, with strict adherence to HSE Guidelines.



ABRASION RESISTANCE

EN 13845 50,000 cycles

EN 649 Group T



VOC EMISSIONS

AgBB VOC test: Pass
(Low Result)



ENVIRONMENTALLY PREFERABLE FLOORING

Vinyl safety flooring has a generic BRE Global A+/A Rating in the Green Guide to Specification, for contract applications. Polysafe Wood FX is 100% recyclable. A full Environmental Report detailing Polyflor's achievements in areas such as recycling, energy reduction and waste avoidance can be found at www.polyflor.com/environment



ELECTRICAL BEHAVIOUR

(body voltage)

EN 1815 ≤2kV

Classified as 'antistatic'



RESISTANCE TO CHEMICALS

Good resistance to dilute acids and alkalis. Chemical resistance charts available on request.



HYGIENE

Contains antimicrobial agents. Independently tested - inhibits growth of MRSA on flooring. Effective maintenance is a key defence against infection.



Polysafe Wood FX is reinforced with polyurethane for improved cleaning and maintenance. As with all Polysafe products, Polysafe Wood FX should not have a polish applied.



APPLICATIONS

Polysafe Wood FX is ideal for use in busy front of house public areas which are normally dry but where there is a risk that water spillage can occur, making slip resistance an important consideration. Typical areas include corridors and circulation areas, receptions, hospital wards, classrooms, shops and cafes as well as social housing applications and normal back of house safety areas. This includes washrooms, WCs, bar serveries and changing rooms. For continually wet areas please refer to our Polysafe Hydro range.



Polysafe safety flooring ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For clarification and for information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com. At the date of issue the data presented is correct. However, Polyflor Ltd. reserves the right to make changes which do not adversely affect performance or quality.

* For clarification regarding slip resistance, consult Polyflor.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM
UK SAMPLE REQUESTS: +44 (0)161 767 2551

James Halstead
FLOORING



August 2009




POLYFLOR
POLYSAFE™
WOOD FX

SAFETY FLOORING

PERFORMANCE AND PROPERTIES

A+BRE
GENERIC ENVIRONMENTAL RATING

Refer to BRE Global ratings on www.thegreenguide.org.uk



POLYFLOR™
COVERING THE WORLD