

Robex Group

TECHNICAL DATA/ INSTRUCTION SHEET

TOUGHSEAL UVC

Description

A two pack polyurethane sealer, providing excellent UV protection available in clear or various colours.

Uses

- As a UV stable, coloured finish coat in the Deckshield membrane and intermediate system.
- The Deckshield system can be applied over concrete, screeds or asphalt to provide a slip resistant wearing surface.
- As a concrete coating with high abrasion & wear resistance.

Benefits

- Easy to apply.
- Light stable-does not yellow.
- Non slip finish can be tailored to requirements.
- High abrasion resistance.
- Fast installation.
- Exceptional mar & scratch resistance.

Coverage

8-10 sq m/ℓ per coat.

Model Specification

Product: Toughseal UVC
Finish: Gloss
Thickness: 50 micron D.F.T/coat
Colour: Various (As per colour chart)

Preparatory work and application in accordance with supplier's instructions.

Standard Colour Chart

- Yellow
- Forest Green
- Dark Grey
- Tile Red
- Mid Grey
- Black

* Also available in white and clear

Statements made herein regarding the capabilities and performance of this product are expressions of the company's expectations based on field experience. To the best of our knowledge this information is reliable and accurate, however, the buyer must rely on his own skill and judgement in assessing suitability to the application. Robex accepts no liability for losses howsoever incurred arising from the Buyer's use of this product.