



CK 200205166623

VERSA PRIMER
PLASTER PRIMER
PRODUCT DATA SHEET

Valdisole

704 - 706 6th Street

Wynberg

Santon 2090

Tel: (011) 885 3136

Fax: (011) 885 1719

**1. RECOMMENDED
USES**

- 1.1. An Alkali resistant primer for use on new dry surfaces such as gypsum plaster, cement plaster and porous concrete surfaces.

2. PREPARATION

- 2.1. Surfaces must be clean and free from loose material.
2.2. Can be thinned up to 20% with Mineral Turps to aid penetration.

3. APPLICATION

- 3.1. Apply a single coat with either a roller or brush ensuring that the product is evenly spread and all areas are covered.

**4. PRODUCT
DATA**

TYPE	Modify Alkyd Resin
DFT/Coat	Min 25µm. Max 30µm
DRYING TIME	Surface Dry 3-4 Hours Hard Dry 16-20 hours at 25°C
VISCOSITY (Sheen Cup)	65-70 Krebs Units
SPECIFIC GRAVITY	1,31-1,33
SOLIDS BY MASS	75%
SPREADING RATE	8-10m ² / (LITRE) depending on surface porosity and type
FINISH	Matt
CLEANUP	Mineral Turps

5. COLOUR

- 5.1. Off white.

6. PRECAUTIONS

- 6.1. Do not apply to metal surfaces.
6.2. Do not paint in wet or cold weather (Minimum 5° Celcius)
6.3. For the best results the coated Plaster Primer surfaces should be over Coated within 72 hours.

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods off application, location and condition of the substrates being coated are beyond our control.